

Explosion Proof Non Armoured Gland



RP... Series

Technical Data

II 2 GD EX d IIC T6 IP67

Compliance with essential health and safety requirements has assured by compliance with:

EN 60079-0

EN 60079-1

EN 60079-7

Features

Gland Material Brass (Nickel Plated) / Stainless Steel/Carbon steel/Aluminium

Seal material Thermoplastic elastomer (Silicone /PVC/NBR/Viton on request)

When used in increased safety applications, This cable gland may be used with braided cable

Where the braid and the cables outer sheath pass in to the enclosure

More Option

Locknut, Earth tag, Sealing washer, O-ring, Shroud

www.alka.ir

CABLE GLAND SELECTION TABLE

Dimensions (mm)				
Inner sheath A				
METRIC	PG	NPT	Min.	Max.
M16	PG9-PG11	3/8"	3.0	8.0
M20 S	PG13/5	1/2"	7.5	11.9
M20 A	PG16	3/4" 1/2"	11.0	14.3
M25	PG21	3/4"	13.0	20.2
M32	PG29	1"	19.0	26.5
M40	PG36	1 1/4"	25.0	32.5
M50	PG42	1 1/2"	31.5	42.5
M63	PG48	2"	42.5	54.3
M75	-	2 1/2"	54.5	65.3
M90	-	3"	67	77.6
M100	-	4"	75.0	91.6

